



Gas Airless Sprayers

The Industry Leader in Innovation, Power and Performance.



PROVEN QUALITY. LEADING TECHNOLOGY.

Gas Airless Sprayers



Unmatched Power and Performance in Gas Airless Sprayers



GMAX™ 3400

GMAX II 3900

GMAX II 5900

GMAX II 5900 Convertible

GMAX II 7900

IronMan 500G

GH™ 130 Convertible

GH 200 Convertible

GH 230 Convertible

GH 300

GH 733 & Roof Rigs™

GH 833 Big Rig™



"We only use Graco sprayers and would never think of using any unit that isn't blue."

- Mike Smith -

Swanson & Youngdale Painting
Minneapolis, MN



**We Stand Behind the Quality
Built Into Every Product**

Only Graco delivers the industry's first choice for gas airless sprayers, backed by a solid reputation for proven quality, maximum performance, reliable warranty coverage and unmatched on-the-job productivity. Graco sprayers are designed to exceed the professional painting contractor's standards for quality and performance.



Proven Quality

- Precision design, 100% factory-tested, and field-proven.
- Consistent improvements on cutting-edge technology keep Graco sprayers running on the job for years.

Maximum Performance

- Higher output with superior control ensures highest quality finish for every job.
- Rely on any of these high performance sprayers to deliver the results you expect from a Graco.

Longest Warranty

- Every Graco gas sprayer is backed by our full warranty coverage and more than 80 years of proven commitment to the professional contractor.
- Sprayers so reliable you may never need to use the warranty.

Unmatched Productivity

- Industry leading features make transport, set-up, operation and clean-up simple and less time-consuming.
- Exclusive Endurance™ Pumps deliver long life, reliable performance, and consistent spraying.
- The Endurance Advantage™ Program eliminates downtime by keeping a spare pump on hand for a quick change-out on the job.

GMAX 3400

The GMAX 3400 is the perfect sprayer for the entry-level contractor who is looking for maximum power in a light weight portable package.

Exclusive Endurance™ Pump

- Long-life V-Max Blue™ Packings, Chromex Rod and case hardened cylinder
- QuikAccess™ intake valve to easily clean or clear debris

Honda® Power

- 120 cc to deliver maximum performance
- Contractor preferred engine with Oil Alert

Light Weight Design

- Graco's lightest professional gas sprayer at only 89 lbs (40.4 kg)
- Easy to load and unload on job sites

Single-Stage Gear Drive System

- Quiet running gear system
- Long life drive system prevents down time
- Light weight design
- Fewer parts to maintain, less service requirements

Electronic Pressure Control System

- Consistent spray with all materials
- Excellent spray pattern provides a high quality finish

Chrome Plated, Welded Steel Cart

- Rugged welded steel construction
- Integrated hose rack with retractable handle
- Lift handles offer convenient grab points
- Tubed pneumatic wheels roll easily on all surfaces

Easy Out™ Pump Filter

- Filtering reduces tip clogs and ensures a quality finish
- Easy Out design filters from the inside out – so filters won't get stuck or collapse when dirty
- Filter removes with the cap for less mess



DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
GMAX 3400 Hi-Boy Complete	248664	0.027	.75 (2.8)	3300 (227)
GMAX 3400 Lo-Boy Complete	248666	0.027	.75 (2.8)	3300 (227)

All units include: New Contractor™ Gun, 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax™ II Hose, RAC® X 517 Tip and Guard, Whip Hose.



Single-stage gear drive provides increased performance with less weight.



Electronic Pressure Control provides high quality spray pattern.



Inlet tube removes by hand for easy clean up.

The GMAX II 3900 is the perfect sprayer for the professional contractor who is working on new residential construction job sites.

Proven Endurance Pump

- Exclusive ProConnect™ system allows quick change-out of pumps – no tools required
- Long-life V-Max Blue Packings, Chromex Rod, and Hardened Stainless Steel cylinder
- QuikAccess intake valve to easily clean or clear debris

Honda Power

- 120 cc to deliver maximum performance
- Contractor preferred engine with Oil Alert

SmartControl Pressure Control

- Advanced microprocessor control delivers Graco's most consistent spray fan at all spraying pressures
 - WatchDog™ system automatically shuts off sprayer when bucket is empty to prevent damage

Exclusive Advantage Drive™ System

- Time-tested drive system provides peace of mind
- Lifetime guarantee
- Hardened helical gears are quiet running
- Auto adjust/alignment system

Chrome Plated, Welded Steel Cart

- Rugged welded steel construction
- Integrated hose rack with retractable handle
- Lift handles offer convenient grab points
- Tubed pneumatic wheels roll easily on all surfaces

Easy Out Pump Filter

- Filtering reduces tip clogs and ensures a quality finish
- Easy Out design filters from the inside out – so filters won't get stuck or collapse when dirty
 - Filter removes with the cap for less mess



GMAX II 3900



Premium Unit Shown

DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
GMAX II 3900 Hi-Boy Standard	248684	0.036	1.25 (4.7)	3300 (227)
GMAX II 3900 Hi-Boy Premium*	248686	0.036	1.25 (4.7)	3300 (227)
GMAX II 3900 Lo-Boy Standard	248683	0.036	1.25 (4.7)	3300 (227)
GMAX II 3900 Lo-Boy Premium*	248685	0.036	1.25 (4.7)	3300 (227)

All units include: New Contractor Gun, 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Hose, RAC X 517 Tip and Guard, Whip Hose.

*Premium units include: AutoClean2, Digital Display and Toolbox.



Exclusive Endurance Advantage Program eliminates downtime.



SmartControl provides high quality spray pattern plus the WatchDog Pump Protection System.



Exclusive ProConnect System – no-tools removal and installation for fast repairs on the job.

GMAX II 5900



Premium Unit Shown

DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
GMAX II 5900 Hi-Boy Standard	248688	0.043	1.6 (6.0)	3300 (227)
GMAX II 5900 Hi-Boy Premium*	248690	0.043	1.6 (6.0)	3300 (227)
GMAX II 5900 Lo-Boy Standard	248687	0.043	1.6 (6.0)	3300 (227)
GMAX II 5900 Lo-Boy Premium*	248689	0.043	1.6 (6.0)	3300 (227)

All units include: New Contractor Gun, 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Hose, RAC X 517 Tip and Guard, Whip Hose.

*Premium units include: AutoClean2, Digital Display and Toolbox.



Exclusive Endurance Advantage Program eliminates downtime.



SmartControl provides high quality spray pattern plus the WatchDog Pump Protection System.



Exclusive ProConnect System – no-tools removal and installation for fast repairs on the job.

The GMAX II 5900 is the most demanded sprayer for the professional contractor spraying new residential/commercial jobs – who knows what it takes to get the job done right, the first time.

Proven Endurance Pump

- Exclusive ProConnect system allows quick change-out of pumps – no tools required
- Long-life V-Max Blue Packings, Chromex Rod, and Hardened Stainless Steel cylinder
- QuikAccess intake valve to easily clean or clear debris

Honda Power

- 160 cc to deliver maximum performance
- Contractor preferred engine with Oil Alert

SmartControl Pressure Control

- Advanced microprocessor control delivers Graco's most consistent spray fan at all spraying pressures
- WatchDog system automatically shuts off sprayer when bucket is empty to prevent damage

Exclusive Advantage Drive™ System

- Time-tested drive system provides peace of mind
- Lifetime guarantee
- Hardened helical gears are quiet running
- Auto adjust/alignment system

Chrome Plated, Welded Steel Cart

- Rugged welded steel construction
- Integrated hose rack with retractable handle
- Lift handles offer convenient grab points
- Tubed pneumatic wheels roll easily on all surfaces

Easy Out Pump Filter

- Filtering reduces tip clogs and ensures a quality finish
- Easy Out design filters from the inside out – so filters won't get stuck or collapse when dirty
- Filter removes with the cap for less mess



The GMAX II 5900 Convertible is the industry's best gas/electric sprayer for the contractor who demands indoor/outdoor flexibility to get the job done.

Proven Endurance Pump

- Exclusive ProConnect system allows quick change-out of pumps – no tools required
- Long-life V-Max Blue Packings, Chromex Rod, and Hardened Stainless Steel cylinder
- QuikAccess intake valve to easily clean or clear debris

Honda Power

- 160 cc to deliver maximum performance
- Contractor preferred engine with Oil Alert

SmartControl Pressure Control

- Advanced microprocessor control delivers Graco's most consistent spray fan at all spraying pressures
 - WatchDog system automatically shuts off sprayer when bucket is empty to prevent damage

Exclusive Advantage Drive System

- Time-tested drive system provides peace of mind
- Lifetime guarantee
- Hardened helical gears are quiet running
- Auto adjust/alignment system

Convertible Power - Electric/Gas

- No-tools change out system is easy to use
- Self-tensioning belt for long life
- Quiet, indoor use not a problem
- 2.0 hp TEFC DC Motor delivers the power

Easy Out Pump Filter

- Filtering reduces tip clogs and ensures a quality finish
- Easy Out design filters from the inside out – so filters won't get stuck or collapse when dirty
- Filter removes with the cap for less mess

GMAX II 5900 Convertible



Premium Unit Shown

DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
GMAX II 5900 Hi-Boy Standard Convertible	248691	0.043	1.6 (6.0)	3300 (227)
GMAX II 5900 Hi-Boy Premium Convertible*	248692	0.043	1.6 (6.0)	3300 (227)
GMAX II 5900 Hi-Boy Standard Convertible w/Electric Motor Kit (Non CSA)	248693	0.043	1.6 (6.0)	3300 (227)
GMAX II 5900 Hi-Boy Standard Convertible w/CSA Electric Motor Kit	248694	0.043	1.6 (6.0)	3300 (227)
GMAX II 5900 Lo-Boy Standard Convertible	248695	0.043	1.6 (6.0)	3300 (227)
GMAX II 5900 Lo-Boy Premium Convertible*	248696	0.043	1.6 (6.0)	3300 (227)
GMAX II 5900 Hi-Boy Premium Convertible* w/Electric Motor Kit (Non CSA)	248889	0.043	1.6 (6.0)	3300 (227)
GMAX II 5900 Lo-Boy Standard Convertible w/Electric Motor Kit (Non CSA)	248697	0.043	1.6 (6.0)	3300 (227)
GMAX II 5900 Lo-Boy Premium Convertible* w/Electric Motor Kit (Non CSA)	248890	0.043	1.6 (6.0)	3300 (227)

NOTE: Electric Motor Max Tip is .031 and Max GPM (LPM) is 1.1 (4.2)
 All units include: New Contractor Gun, 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Hose, RAC X 517 Tip and Guard, Whip Hose.
 *Premium units include: AutoClean2, Digital Display and Toolbox.



Exclusive Endurance Advantage Program eliminates downtime.



Change from gas to electric in seconds without any tools.



Exclusive ProConnect System – no-tools removal and installation for fast repairs on the job.



GMAX II 7900



Premium Unit Shown

DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
GMAX II 7900 Lo-Boy Standard	248700	0.048	2.2 (8.3)	3300 (227)
GMAX II 7900 Lo-Boy Premium*	248702	0.048	2.2 (8.3)	3300 (227)
GMAX II 7900 Hi-Boy Standard	248701	0.048	2.2 (8.3)	3300 (227)
GMAX II 7900 Hi-Boy Premium*	248703	0.048	2.2 (8.3)	3300 (227)
GMAX II 7900 Hi-Boy Roof Rig [^]	248953	0.048	2.2 (8.3)	3300 (227)

All units include: New Contractor Gun, 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Hose, RAC X 517 Tip and Guard, 1/4 in (6.4 mm) Whip Hose.

*Premium units include: AutoClean2, Digital Display and Toolbox.

[^] Roof Rig includes: Heavy Duty Gun, 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Hose, 20 in (50 cm) Fixed Heavy Duty Extension, 1/4 in (6.4 mm) Whip Hose, Hose Swivel and (2) RAC X Tips and Guard.



Exclusive Endurance Advantage Program eliminates downtime.



SmartControl provides high quality spray pattern plus the WatchDog Pump Protection System.



Exclusive ProConnect System – no-tools removal and installation for fast repairs on the job.

The GMAX II 7900 sprayer is the most powerful sprayer for high production paint contractors doing large tract, commercial and new residential construction jobs – where uninterrupted spraying is expected.

Exclusive MaxLife Endurance Pump

- Exclusive MaxLife rod and sleeve delivers unmatched durability and life — Graco's best
- Exclusive ProConnect system allows quick change-out of pumps – no tools required
- QuikAccess Intake Valve to easily clean or clear debris

Honda Power

- 200 cc to deliver maximum performance
- Contractor preferred engine with Oil Alert

SmartControl Pressure Control

- Advanced microprocessor-based control delivers Graco's most consistent spray fan at all spraying pressures
- WatchDog system automatically shuts the pump off when material runs out

Exclusive Advantage Drive System

- Time-tested drive system provides peace of mind
- Lifetime guarantee
- Hardened helical gears are extremely quiet running
- Auto adjust/alignment system

Easy Out Pump Filter

- Filtering reduces tip clogs and ensures a quality finish
- Easy Out design filters from the inside out – so filters won't get stuck or collapse when dirty
- Filter removes with the cap for less mess



Power, durability, and capability is what makes this Graco sprayer an IronMan. From its oversized engine to its rugged, heavy-duty frame, the IronMan is built with extreme ruggedness for the serious contractor.

Extreme-Duty MaxLife HD Pump

- Exclusive MaxLife sleeve and Chromex rod delivers unmatched durability and life
- Long pump design puts the intake in the material – resulting in consistent priming with even the thickest materials
- Oversized clearances ensure minimal pressure drop and increase performance

Increased Honda Power

- 200 cc Honda Engine is oversized for increased performance and long life
- Oil alert shuts the engine down when the oil level is low – saving you from a costly repair

Extreme-Duty Prime Valve

- Designed to hold up to high pressure dumps for the most extreme jobsite conditions

Extreme-Duty Drive

- Lifetime lubricated and guaranteed for life

Extreme-Duty Frame

- “Indy Car” style roll cage protects all critical sprayer components from extreme jobsite abuse on all surfaces

Flat-Proof Tires

- Nails, screws, blades cannot flatten these tires
- Pneumatic tire performance

Crush-Proof Intake Screen

- Holds up to impacts which are common on the jobsite

Control Lock Theft Deterrent

- Allows the user to lock/disable the sprayer – deters jobsite theft
- Protects the controls from jobsite abuse



IronMan 500G



DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
IronMan 500G	256790	0.043	1.6 (6.0)	3300 (227)

Includes: Silver Plus™ Gun, 1/4 in x 50 ft (6.4 mm x 15 m) & 3/8 in x 50 ft (9.5mm x 15 m) BlueMax II Hose, RAC X 527, RAC X 1231 Tip and Guard.



Control lock protects and locks controls



Extreme-duty roll cage frame with a build-in hose wrap



Crush-proof intake screen holds up to jobsite abuse

GH 130 Convertible

The GH 130 Convertible is the clear choice for entry level contractors who demand max power in a small package.

Exclusive Graco Endurance Pump

- Proven design and performance
- Exclusive chromex rod delivers excellent durability and life
- Exclusive QuikChange™ Pump System and QuikAccess Intake Valve eliminates down-time

Honda Power

- 120 cc to deliver maximum performance
- Contractor preferred engine with Oil Alert

High Efficiency Hydraulic Motor

- Faster, more responsive changeover
- High precision pressure control
- 100% O-ring sealed fittings prevents leaks
- Fewer moving parts for easier maintenance and longer life

High Capacity Cooling System

- Innovative hydraulic reservoir design
- Runs more than 20% cooler than competition
- No special hydraulic fluid needed (ISO 46)
- Cooling fins on reservoir deflect heat away from unit
- Easy-to-use drain plug

Convertible Power - Electric/Gas

- No-tools change out system is easy to use
- Self-tensioning belt for long life
- Quiet, indoor use not a problem
- 2.0 hp TEFC DC Motor delivers the power

Easy Out Pump Filter

- Filtering reduces tip clogs and ensures a quality finish
- Easy Out design filters from the inside out – so filters won't get stuck or collapse when dirty
- Filter removes with the cap for less mess



DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
GH 130 Convertible Complete	253957	0.037	1.3 (4.9)	3300 (227)
GH 130 Convertible Complete w/Electric Motor Kit (non CSA)	253959	0.037	1.3 (4.9)	3300 (227)
GH 130 Convertible Complete w/CSA Electric Motor Kit	253980	0.037	1.3 (4.9)	3300 (227)

NOTE: Electric Motor Max Tip is .031 and Max GPM (LPM) is 1.1 (4.2)

All units include: New Contractor Gun, 1/4 in x 50 ft (9.5 mm x 15 m) BlueMax II Hose, RAC X 517 Tip and Guard, Whip Hose.



Convertability allows easy switching from gas to electric in seconds.



Exclusive crush-proof rock catcher provides unmatched pump protection. (patent pending)



Graco hydraulic power – a proven workhorse for long-life and reliability.

The GH 200 Convertible is the solution for medium to large jobs where proven hydraulic power is demanded to get the job done whether inside or outside.

Exclusive MaxLife Endurance Pump

- Exclusive MaxLife rod and sleeve delivers unmatched durability and life – Graco’s best
- Exclusive ProConnect system allows quick change-out of pumps – no tools required
- QuikAccess intake valve to easily clean or clear debris

Honda Power

- 160 cc to deliver maximum performance
- Contractor preferred engine with Oil Alert

High Efficiency Hydraulic Motor

- Faster, more responsive changeover
- High precision pressure control
- 100% O-ring sealed fittings prevents leaks
- Fewer moving parts for easier maintenance and longer life

High Capacity Cooling System

- Innovative hydraulic reservoir design
- Runs more than 20% cooler than competition
- No special hydraulic fluid needed (ISO 46)
- Cooling fins on reservoir deflect heat away from unit
- Easy-to-use drain plug

Easy Out Pump Filter

- Filtering reduces tip clogs and ensures a quality finish
- Easy Out design filters from the inside out – so filters won’t get stuck or collapse when dirty
- Filter removes with the cap for less mess

GH 200 Convertible



DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
GH 200 Convertible Complete	253962	0.047	2.15 (8.14)	3300 (227)
GH 200 Convertible Complete w/Electric Motor Kit (non CSA)	253963	0.047	2.15 (8.14)	3300 (227)
GH 200 Convertible Complete w/CSA Electric Motor Kit	253981	0.047	2.15 (8.14)	3300 (227)

NOTE: Electric Motor Max Tip is .031 and Max GPM (LPM) is 1.1 (4.2)
 All units include: Silver Plus Airless Gun, 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Hose, RAC X 517 Tip and Guard, Whip Hose.



Convertability allows no-tool gas or electric power in seconds.



Exclusive crush-proof rock catcher provides unmatched pump protection. (patent pending)



Exclusive ProConnect System, no-tools pump removal and installation in seconds.



GH 230 Convertible & GH 300



The GH 230 & 300 are two of the most powerful hydraulic sprayers for high production contractors who are spraying a wide range of materials including latex, elastomerics to block fillers on large commercial jobs.

Exclusive MaxLife Endurance Pump

- Exclusive MaxLife rod and sleeve delivers unmatched durability and life – Graco's best
- Exclusive ProConnect system allows quick change-out of pumps – no tools required
- QuikAccess intake valve to easily clean or clear debris

Honda Power

- Delivers maximum performance
- Contractor preferred engine with Oil Alert

High Efficiency Hydraulic Motor

- Faster, more responsive changeover
- High precision pressure control
- 100% O-ring sealed fittings prevents leaks
- Fewer moving parts for easier maintenance and longer life

High Capacity Cooling System

- Innovative hydraulic reservoir design
- Runs more than 20% cooler than competition
- No special hydraulic fluid needed (ISO 46)
- Cooling fins on reservoir deflect heat away from unit
- Easy-to-use drain plug

Easy Out Pump Filter

- Filtering reduces tip clogs and ensures a quality finish
- Easy Out design filters from the inside out – so filters won't get stuck or collapse when dirty
- Filter removes with the cap for less mess

DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
GH 230 Convertible Complete	253965	0.053	2.35 (8.9)	3300 (227)
GH 230 Convertible Complete w/Electric Motor Kit (non CSA)	253966	0.053	2.35 (8.9)	3300 (227)
GH 230 Convertible Complete w/CSA Electric Motor Kit	253982	0.053	2.35 (8.9)	3300 (227)
GH 300 Complete	253968	0.057	3.0 (11.4)	3300 (227)

NOTE: Electric Motor Max Tip is .031 and Max GPM (LPM) is 1.1 (4.2)

All units include: Silver Plus Gun, 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Hose, RAC X 517 Tip and Guard, Whip Hose.



Convertability allows easy switching from gas to electric in seconds.



Exclusive crush-proof rock catcher provides unmatched pump protection. (patent pending)



Exclusive ProConnect System, no-tools pump removal and installation.





The industry's first and only no-tools pump removal and installation system. ProConnect allows you to remove and replace your pump in seconds without ANY tools, saving you time and money on the job.

Combine ProConnect with Graco's Endurance Advantage Program and you now have the ability to stay spraying, preventing costly downtime. No one else comes close! Experience the power of ProConnect today.

GMAX II and GH ProConnect System



ProConnect system **CLOSED** with pump in.



ProConnect system **OPEN** with pump in.



ProConnect system **OPEN** without pump in.

You can find the exclusive ProConnect System on these Graco sprayers!



GH 200 Convertible



GH 230 Convertible



GH 300



GMAX II 3900



GMAX II 5900



GMAX II 7900

GH 833

The gas hydraulic unit that can spray it all – the GH 833 “Big Rig”. The GH 833 is the answer for high production professional contractors who demand uninterrupted performance with the widest range of materials.



Bare Unit Shown



Exclusive MaxLife Endurance Pump

- Proven design and performance
- Exclusive MaxLife rod and sleeve delivers unmatched durability and life – Graco’s best
- Exclusive QuikChange Pump System and QuikAccess Intake Valve eliminates down-time
- Only 16 cycles per gallon

Honda Power

- 390 cc to deliver maximum performance
- Contractor preferred engine with Oil Alert

Heavy Duty Graco Hydraulic System

- Faster, more responsive changeover
- O-ring sealed for fewer leaks
- High-precision pressure control
- No hydraulic reset button needed
- Durable hydraulic lines for long life

Heavy Duty Cooling System

- Large 4-gallon hydraulic reservoir
- Large durable return line hydraulic filter extends life
- No special hydraulic fluid needed
- Proven cooler and blower system
- Easy-to-use drain plug

Heavy Duty Frame

- Multi-function design converts to skid mount in seconds
- Enamel painted steel tubing - corrosion protection
- Easy-roll tubed pneumatic tires

Easy Out Pump Filter

- Filtering reduces tip clogs and ensures a quality finish
- Easy Out design filters from the inside out – so filters won’t get stuck or collapse when dirty
- Filter removes with the cap for less mess

Additional Features

- Lockable pressure control knob
- Grounding wire for safety with solvent materials
- Huge 1.5 inch diameter siphon hose
- Huge 1 inch porting on displacement pump

DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
GH 833 Bare (390 cc)	249318	0.065	4.0 (15.1)	4000 (276)
GH 833 Complete*	249617	0.065	4.0 (15.1)	4000 (276)
GH 833 OEM (Hydraulic Motor & Displacement pump only)	249767	0.065	4.0 (15.1)	4000 (276)
GH 833 Direct Immersion Kit	287843	0.065	4.0 (15.1)	4000 (276)

*Complete units include: Silver Plus Gun, 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II HP 4000 psi (276 bar) Hose, RAC X 655 Tip and Guard, 1/4 in x 3 ft, 4000 psi (276 bar) Whip Hose.



Exclusive QuikChange Pump System and QuikAccess Intake Valve eliminates down-time.



Direct Immersion Kit allows ultimate flexibility with tough-to-spray materials.



5-gallon direct immersion for the heaviest, most difficult coatings.

GH 833 Direct Immersion Kit

Only Graco offers the flexibility and reliability needed to complete the toughest jobs with the widest range of materials.

When the temperature drops or when materials are more difficult to spray,

turn to the GH 833

Direct Immersion Kit.

In a matter of minutes you can convert your GH 833 into a direct immersion workhorse unit. Now you can spray it all – only with Graco.



GH 833 Direct Immersion Kit
Part #287843



Application Chart

GRACO SPRAYER	Latex Paints	Primers	Block Fillers	Enamel	Electromerics	Acrylic: Water / Solvent	Epoxy: Finish / Solvent	Polyester	Coal/Tar	Polyurethane	Sealers	Lacquers	Varnishes	Bridge Paints (No Zinc Base)	Asphalt Emulsion: fibered / non fibered	Mastics - Adhesive type	Waterproofing / Above and Below grade	Asphalt cut-back: fibered / non fibered	Contact Cement	Texture: Smooth & Fine	Burntastics	MonoPerm	Aluminum Emulsion: fibered / non fibered	Elastomeric Acrylic Emulsion Primer
GMAX II 7900 RR	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
GH 733	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
GH 833	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
GH 1015	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
GH 2075	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
GH 2560	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
GH 3640	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
GH 5030	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

Sprayable Coatings

- Architectural
- Protective
- Industrial
- Other: Roofing

*Note: Materials and temperatures may dictate the hose length you can use.

GH 733 & Roof Rigs



Bare Unit Shown

DESCRIPTION	PART NUMBER	MAX GPM (LPM)	MAX PSI (BAR)
GH 733 Bare	231733	3.0 (11.4)	3500 (241)
GH 733 Complete*	230975	3.0 (11.4)	3500 (241)
GH 1015 Bare Roof Rig	965165	15.0 (56.7)	1000 (70)
GH 2075 Bare Roof Rig	965171	7.5 (28.2)	1800 (124)
GH 2560 Bare Roof Rig	965168	6.0 (22.7)	2400 (166)
GH 3640 Bare Roof Rig	687327	3.8 (14.4)	3600 (245)
GH 5030 Bare Roof Rig	687100	2.8 (10.5)	4900 (337)

*Complete units include: Silver Plus Gun, 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II HP 4000 psi (276 bar) Hose, RAC X 517 Tip and Guard, 1/4 in x 3 ft, 4000 psi (276 bar) Whip Hose.



Graco Hydraulic System – a proven workhorse for long-life and reliability.



6 interchangeable pumps allows maximum versatility for all applications.



No job is too big for the GH 733 Roof Rig.

For more than 20 years contractors have turned to the GH 733 & Roof Rigs when they need to spray some of the most aggressive materials found today.

The GH 733 & Roof Rigs are simply some of the most powerful and versatile units in the market.

Exclusive Xtreme™ Pump

- QuikChange pump section
- Time tested durability and performance
- Long life XtremeSeals™ and leather packings
- Heavy duty piston rod for long life
- QuikAccess intake valve removes easily for fast repairs

Kohler® Power

- Reliable electric start system
- 624 cc to deliver maximum power
- Air-cooled twin cylinder keeps heat away
- Time-tested power source

Heavy Duty Graco Hydraulic System

- Faster, more responsive changeover
- O-ring sealed for fewer leaks
- Motor reset button to correct stalling
- Easy-to-service design
- Durable large hydraulic lines for long life

Heavy Duty Cooling System

- Large 5-gallon hydraulic reservoir
- Large return line hydraulic filter
- No special hydraulic fluid needed
- Proven cooler and blower system
- Easy-to-use hydraulic drain plug

Heavy Duty Frame

- Field proven design withstands abuse
- 2-inch diameter steel tubing
- Tall, easy to roll transport tires
- Ergonomic design is easy to service

Additional Features

- Lockable pressure control knob
- Grounding wire for safety with solvent materials
- Durable bypass valve
- Adjustable intake ball travel system and interchangeable displacement pumps for a wide variety of spray applications



Purchase any Graco Gas Sprayer and you can purchase an Endurance Pump for up to 80% off list price. Keep a spare pump on hand to save yourself time and money on every job.

If you'd rather repack your own pump, we'll let you choose a free Repair Kit instead. With reliability you can count on, Graco ensures you'll always be up and spraying! Follow the registration instructions included with your sprayer.



Endurance Pump

Warranty

* Lifetime Electric Motor Warranty

If the Motor fails from normal use, we'll replace it under warranty for the original owner for the life of the sprayer.

Lifetime Drive Warranty

If the Drive Train fails from normal use, we'll replace it under warranty for the original owner for the life of the sprayer.

* 3-Year Warranty

Coverage against defects in materials and workmanship on the entire sprayer.

* 30-Day "Just Add Paint" Replacement Guarantee

Dissatisfied? Simply return the sprayer to the place you bought it within 30 days. They'll either exchange it for an identical sprayer or you can trade up to a larger sprayer at an extra cost.

* Downtime Eliminator Program

Part needed for a warranty repair not in stock at your distributor?

Get FREE next business day air freight delivery when distributor orders the part by 2 p.m. CST.



ProConnect no-tools pump removal and installation system makes Endurance Pump swap out fast and easy.



Downtime Costs You Money

- Inconvenient Turnaround Time
- Unplanned and Expensive Rental Expenses
- Inconvenient and Costly Service Center Trips
- Lost Hours and Dollars in Idle Manpower

Our Commitment To Productivity

- Exclusive ProConnect System
- Exclusive QuikChange Lower
- Quick Replacement
- No Special Tools Required
- You are Up and Spraying in Minutes, Not Days

* North American only. See local Graco distributors for Country specifics.

Accessories

For GMAX II & GH 130 - 300

RAC X TIPS AND GUARDS



LTX-XXX

RAC[®] X SwitchTips, Blue (Odd #)

It has the longest lasting fan pattern on the market. Max Working Pressure: 4050 psi (279 bar, 27.9 MPa)

WR-XXXX

RAC X WideRAC[®] SwitchTips, Blue (Odd #)

24 in (610 mm) spray fan for maximum coverage. Max Working Pressure: 4050 psi (279 bar, 27.9 MPa)

246215

RAC X HandTite Guard — 7/8 in (22 mm) thread size, standard Graco thread

246437

RAC X HandTite Guard — 11/16 in (17 mm) thread size, older style Graco Pole Guns, fits competitive guns with 11/16 in threads

RAC 5 TIPS AND GUARDS



286-XXX

RAC 5 SwitchTips, Black (Odd #)

Ideal for residential, commercial and industrial jobs. MWP: 4050 psi (279 bar, 27.9 MPa)

243161

RAC 5 HandTite Guard — 7/8 in (22 mm) thread size, standard Graco thread

243263

RAC 5 HandTite Guard — 11/16 in (17 mm) thread size, older style Graco Pole Guns, fits competitive guns with 11/16 in threads

NEW CONTRACTOR & FTx GUNS



288420

Maximum Working Pressure: 3600 psi (248 bar, 24.8 MPa)

Contractor Gun (2-finger) with RAC X 517 SwitchTip and Guard

288425

Contractor Gun (4-finger) with RAC X 517 SwitchTip and Guard

288421

Contractor Gun (2-finger) with RAC 5 517 SwitchTip

288430

FTx[™] Gun (4-finger) with RAC X 515 SwitchTip and Guard

288429

FTx Gun (2-finger) with RAC X 515 SwitchTip and Guard

288431

FTx Gun (4-finger) with RAC 5 515 SwitchTip

288488

Gun Repair Kit

SILVER PLUS GUN



246240

Maximum Working Pressure: 5000 psi (345 bar, 34.5 MPa)

Silver Plus Gun (2-finger) with RAC X 517 SwitchTip and Guard

243283

Silver Plus Gun (2-finger) with RAC 5 517 SwitchTip and Guard

235460

Silver Plus Gun (2-finger) with Flat Tip Guard

235461

Silver Plus Gun (4-finger) with Flat Tip Guard

235462

Silver Plus Gun Fine Finish (2-finger) with Flat Tip Guard

235474

Repair Kit

HEAVY DUTY GUN



241705

Maximum Working Pressure: 4000 psi (276 bar, 27.6 MPa) — Fluid Orifice Diameter: 0.125 in (3.2 mm)

Heavy Duty Gun with RAC X 531 Spray Tip and Tip Guard

Ideal for high solids, mastics, protective coatings and smooth textures

237260

Repair Kit

Accessories

For GMAX II & GH 130 - 300

GUN HOSE KITS



288489
288490
288493
287095
287041
287042

Includes the following unless otherwise noted: Airless Gun, RAC X 517 SwitchTip and Guard, 1/4 in x 50 ft (6.4 mm x 15 m) 3300 psi (227 bar) BlueMax™ II Airless Hose and 3 ft (0.9 m) Whip Hose

Contractor Gun Hose Kit
Contractor Gun Hose Kit — 3/8 in x 50 ft (9.5 mm x 15 m) Airless Hose
FTx Gun Hose Kit — 515 Tip
Flex Plus Gun Hose Kit
Silver Plus Gun Hose Kit
Silver Plus Gun Hose Kit — 3/8 in x 50 ft (9.5 mm x 15 m) Airless Hose

BLUEMAX II AIRLESS HOSE



238358
238959
238359
240793
240794
240796
240797

Feel the Difference in flexibility!

3/16 in x 3 ft (4.8 mm x 0.9 m) BlueMax II 3300 psi Airless Whip Hose
3/16 in x 4.5 ft (4.8 mm x 1.4 m) BlueMax II 3300 psi Airless Whip Hose
3/16 in x 6 ft (4.8 mm x 1.8 m) BlueMax II 3300 psi Airless Whip Hose
1/4 in x 25 ft (6.4 mm x 7.5 m) BlueMax II 3300 psi Airless Hose
1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II 3300 psi Airless Hose
3/8 in x 25 ft (9.5 mm x 7.5 m) BlueMax II 3300 psi Airless Hose
3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II 3300 psi Airless Hose

BLUEMAX II HIGH PRESSURE HOSE



277249
277250
277351
277251
277253

4000 psi WPR

1/4 in x 3 ft (6.4 mm x 0.9 m) MxF Whip Hose
1/4 in x 50 ft (6.4 mm x 15 m) FBE
3/8 in x 3 ft (9.5 mm x 0.9 m) MxF Whip Hose
3/8 in x 50 ft (9.5 mm x 15 m) FBE
1/2 in x 50 ft (13 mm x 15 m) FBE

POLE GUNS



287023
287024

MWP: 3600 psi (248 bar, 24.8 MPa)

3 ft (.9 m) Pole Gun with RAC X SwitchTip 517 System
6 ft (1.8 m) Pole Gun with RAC X SwitchTip 517 System

EXTENSIONS



287019
287020
287021
287022

RAC X Tip Extensions - Maximum WPR: 4050 psi, (280 bar, 28.0 MPa)

Includes: RAC X HandTite Guard Standard with 7/8 in (22 mm) Gun Nut and OneSeal

10 in (25 cm)
15 in (38 cm)
20 in (50 cm)
30 in (75 cm)

KITS

287541
245249
208259
245508
245250

55 gallon Siphon Kit, 1.25 in diameter x 6 ft Siphon Hose, for GMAX II 3900/5900/7900
55 gallon Siphon Kit, 1.25 in diameter x 6 ft Siphon Hose, for GMax 7900, HydraMax 225 - old style
55 gallon Siphon Kit, 1.25 in diameter x 6 ft Siphon Hose, for 3900/5900 - old style GMax
30 gallon Siphon Kit, 1.25 in diameter x 6 ft Siphon Hose, for 3900/5900 - old style GMax
55 gallon Siphon Kit, 1.25 in diameter x 6 ft Siphon Hose, for HydraMax 300/350

Accessories

For GH 733 & GH 833

AIRLESS GUNS & GUN HOSE KITS



- 246240 Silver Plus Gun (2-Finger) with RAC X 517 SwitchTip and Guard
- 241705 Heavy Duty Gun with RAC X 531 SwitchTip and Guard
- 224472 Mastic Gun 5000 psi (345 bar) with 36 in (.9 m) extension
- 287850 Silver Plus Gun Hose Kit with RAC X SwitchTip, 3/8 in (9.5 mm) x 50 ft (15 m) 3300 psi (227 bar) Hose
- 287851 Flex Plus Gun Hose Kit with RAC X 655 and 531 SwitchTip, 3/8 in (9.5 mm) x 50 ft (15 m) 4000 psi (276 bar) Hose and Whip Hose
- 287852 Heavy Duty Gun Hose Kit with RAC X 655 and 531 SwitchTip, 3/8 in (9.5 mm) x 50 ft (15 m) 4000 psi (276 bar) Hose
- 189018 Gun Swivel rated to 5600 psi (386 bar, 38.6 MPa)

RAC X TIPS AND GUARDS



- LTXxxx RAC X SwitchTips, Blue (Odd #)
Ideal for residential, commercial and industrial jobs. MWP: 4050 psi (280 bar, 28.0 MPa)
- 246215 RAC X HandTite™ Tip Guard — 7/8 in (22 mm) thread size
- 246437 RAC X HandTite Tip Guard — 11/16 in (17.5 mm) thread size

RAC 5 TIPS AND GUARDS



- 286xxx RAC 5 SwitchTips, Black (Odd #)
Ideal for residential, commercial and industrial jobs. MWP: 4050 psi (279 bar, 27.9 MPa)
- 243161 RAC 5 HandTite Guard — 7/8 in (22 mm) thread size
- 243263 RAC 5 HandTite Guard — 11/16 in (17.5 mm) thread size

BLUEMAX II HIGH PRESSURE HOSE



- Synthetic-braided, 4000 psi (276 bar, 27.6 MPa) maximum working pressure rated at 180° F (82.2° C)
- 277249 1/4 in x 3 ft (6.4 mm x 0.9 m) MxF Whip Hose
- 277250 1/4 in x 50 ft (6.4 mm x 15 m) FBE
- 277351 3/8 in x 3 ft (9.5 mm x 0.9 m) MxF Whip Hose
- 277253 3/8 in x 50 ft (9.5 mm x 15 m) FBE
- 277251 1/2 in x 50 ft (13 mm x 15 m) FBE

Accessories

For GH 733 & GH 833

GH 733 & GH 833 KITS

287843	Direct Immersion Kit — includes: Hydraulic Feed Lines, Stinger Tube and Lift Bracket
249767	OEM Kit — includes: Hydraulic Motor/Head, Displacement Pump
287916	Non-Solvent Siphon Kit, 1.5 in diameter x 6.5 ft Siphon Hose
287936	Non-Solvent Siphon Kit, 2 in diameter x 6.5 ft Siphon Hose
287915	Solvent Resistant Siphon Kit, 1.5 in diameter x 6.5 ft Siphon Hose
948727	2 in (50 mm) Siphon Kit adapts to any GH 733, Bulldog® or King® Pump air or gas
948740	Lift Kit modifies GH 733 with version code A, B or C to accept GH 1015, GH 2075 or GH 2560 pump lowers
245244	Lift Kit modifies GH 733 with version code A, B or C to accept Xtreme pump lower kits (GH 733, GH 3640 and GH 5030 pump kits)

FITTINGS



156971	1/4 in npt x 1/4 in npt (6.4 mm x 6.4 mm) – MBE Maximum Working Pressure: 7500 psi (517 bar, 51.7 MPa)
156849	3/8 in npt x 3/8 in npt (9.5 mm x 9.5 mm) – MBE Maximum Working Pressure: 6000 psi (420 bar, 42.0 MPa)
158491	1/2 in npt x 1/2 in npt (13 mm x 13 mm) – MBE Maximum Working Pressure: 6700 psi (462 bar, 46.2 MPa)
155865	1/2 in npt x 1/2 in npsm (13 mm x 13 mm) – FBE Maximum Working Pressure: 5000 psi (345 bar, 34.5 MPa)
157350	1/4 in npt x 3/8 in npt (6.4 mm x 9.5 mm) – MBE Maximum Working Pressure: 5000 psi (345 bar, 34.5 MPa)
159239	1/2 in npt x 3/8 in npt (13 mm x 9.5 mm) – MBE Maximum Working Pressure: 5000 psi (345 bar, 34.5 MPa)
15H335	1.0 in npt x 3/8 in npt (25.4 mm x 9.5 mm) – MBE Maximum Working Pressure: 5000 psi (345 bar, 34.5 MPa)

UNIONS



156823	1/4 in npt(m) x 1/4 in npsm(f) (6.4 mm x 6.4 mm) Maximum Working Pressure: 5000 psi (345 bar, 34.5 MPa)
155665	3/8 in npt(m) x 3/8 in npsm(f) (9.5 mm x 9.5 mm) Maximum Working Pressure: 5000 psi (345 bar, 34.5 MPa)
157705	1/4 in npt(m) x 3/8 in npsm(f) (6.4 mm x 9.5 mm) Maximum Working Pressure: 5000 psi (345 bar, 34.5 MPa)
155570	1/4 in npt(f) x 1/4 in npsm(f) (6.4 mm x 9.5 mm) Maximum Working Pressure: 5000 psi (345 bar, 34.5 MPa)
159153	3/8 in npt(f) x 1/4 in npsm(f) (9.5 mm x 6.4 mm) Maximum Working Pressure: 5000 psi (345 bar, 34.5 MPa)

Gas Product Specifications



GMAX 3400

- Max Tip:** .027
Max psi/bar: 3300/227
Max gpm/lpm: .75/2.8
Engine: 120 cc Honda
Weight lbs/kg: 89/40.4
Gun Support:
 (1) Gun with .027
Gun:
 • Contractor Airless Gun
Hose:
 • 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II 3300 psi (227 bar)
Tip:
 • RAC X 517 Tip and Guard
Inlet Strainer:
 • Part #246385
Pump Filter:
 • Includes Easy Out Pump Filter
Easy Out Filter Screens:
 • 30 Mesh - 244071
 • 60 Mesh - 244067
 • 100 Mesh - 244068
 • 200 Mesh - 244069
Sprayer Dimensions:
 • 31 (79) x 22.5 (58) x 31.5 (80)
Wear Parts:
 • Packing Kit - 244194
 • Chromex Rod - 249125
 • Cylinder - 243176
 • Intake Valve - 246429
 • Piston Valve - 239937
Complete Pump Lower:
 • Part #246428
Manuals:
 • Instruction - 310802
 • Repair - 310813



GMAX II 3900

- Max Tip:** .036
Max psi/bar: 3300/227
Max gpm/lpm: 1.25/4.7
Engine: 120 cc Honda
Weight lbs/kg: 109/50
Gun Support:
 (1) Gun with .036
 (2) Guns with .023
Gun:
 • Contractor Airless Gun
Hose:
 • 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II 3300 psi (227 bar)
Tip:
 • RAC X 517 Tip and Guard
Inlet Strainer:
 • Part #189920
Pump Filter:
 • Includes Easy Out Pump Filter
Easy Out Filter Screens:
 • 30 Mesh - 244071
 • 60 Mesh - 244067
 • 100 Mesh - 244068
 • 200 Mesh - 244069
Sprayer Dimensions:
 • 32 (81) x 22.25 (56.5) x 31.5 (80)
Wear Parts:
 • Packing Kit - 248212
 • Chromex Rod - 248206
 • Cylinder - 287551
 • Sleeve - 248209
 • Piston Valve - 239937
 • Intake Valve - 246429
 • 30/55 Gallon Siphon Kit - 287541
Complete Pump Lower:
 • Part #287512
Manuals:
 • Instruction - 310892
 • Repair - 310893



GMAX II 5900

- Max Tip:** .043
Max psi/bar: 3300/227
Max gpm/lpm: 1.6/6.0
Engine: 160 cc Honda
Weight lbs/kg: 139/64
Gun Support:
 (1) Gun with .043
 (2) Guns with .029
 (3) Guns with .023
Gun:
 • Contractor Airless Gun
Hose:
 • 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II 3300 psi (227 bar)
Tip:
 • RAC X 517 Tip and Guard
Inlet Strainer:
 • Part #189920
Pump Filter:
 • Includes Easy Out Pump Filter
Easy Out Filter Screens:
 • 30 Mesh - 244071
 • 60 Mesh - 244067
 • 100 Mesh - 244068
 • 200 Mesh - 244069
Sprayer Dimensions:
 • 32.25 (81.9) x 24.5 (62) x 32.25 (82)
Wear Parts:
 • Packing Kit - 248213
 • Chromex Rod - 248207
 • Cylinder - 287552
 • Sleeve - 248210
 • Piston Valve - 240150
 • Intake Valve - 244199
 • 30/55 Gallon Siphon Kit - 287541
Complete Pump Lower:
 • Part #287513
 • 5900HD #287579
Manuals:
 • Instruction - 310892
 • Repair - 310893



GMAX II 5900 Convertible

- Max Tip:** .043
Max psi/bar: 3300/227
Max gpm/lpm: 1.6/6.0
Engine: 160 cc Honda
Weight lbs/kg: 146/67
Electric Max Tip: .031
Electric Max Gpm/Lpm: 1.1/4.2
Gun Support: (Gas)
 (1) Gun with .043
 (2) Guns with .029
 (3) Guns with .023
Gun:
 • Contractor Airless Gun
Gun Support: (Electric)
 (1) Gun with .031
 (2) Guns with .017
Hose:
 • 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II 3300 psi (227 bar)
Tip:
 • RAC X 517 Tip and Guard
Inlet Strainer:
 • Part #189920
Pump Filter:
 • Includes Easy Out Pump Filter
Easy Out Filter Screens:
 • 30 Mesh - 244071
 • 60 Mesh - 244067
 • 100 Mesh - 244068
 • 200 Mesh - 244069
Sprayer Dimensions:
 • 32.25 (81.9) x 24.5 (62) x 32.25 (82)
Wear Parts:
 • Packing Kit - 248213
 • Chromex Rod - 248207
 • Cylinder - 287552
 • Sleeve - 248210
 • Intake Valve - 244199
 • Piston Valve - 240150
 • 30/55 Gallon Siphon Kit - 287541
Complete Pump Lower:
 • Part #287513
Manuals:
 • Instruction - 310892
 • Repair - 311046



GMAX II 7900

- Max Tip:** .048
Max psi/bar: 3300/227
Max gpm/lpm: 2.2/8.3
Engine: 200 cc Honda
Weight lbs/kg: 146/67
Gun Support:
 (1) Gun with .048
 (2) Guns with .035
 (3) Guns with .027
 (4) Guns with .023
Gun:
 • Contractor Airless Gun
Hose:
 • 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II 3300 psi (227 bar)
Tip:
 • RAC X 517 Tip and Guard
Inlet Strainer:
 • Part #189920
Pump Filter:
 • Includes Easy Out Pump Filter
Easy Out Filter Screens:
 • 30 Mesh - 244071
 • 60 Mesh - 244067
 • 100 Mesh - 244068
 • 200 Mesh - 244069
Sprayer Dimensions:
 • 33 (83.8) x 24.5 (62) x 32.25 (82)
Wear Parts:
 • Packing Kit - 249123
 • MaxLife Rod - 249119
 • Cylinder - 249139
 • MaxLife Sleeve - 249121
 • Intake Valve - 240918
 • Piston Valve - 249177
 • 30/55 Gallon Siphon Kit - 287541
Complete Pump Lower:
 • Part #249122
Manuals:
 • Instruction - 310892
 • Repair - 310893



IronMan 500G

- Max Tip:** .043
Max psi/bar: 3300/227
Max gpm/lpm: 1.6/6.0
Engine: 200 cc Honda
Weight lbs/kg: 168/76
Gun Support: (Gas)
 (1) Gun with .043
 (2) Guns with .029
 (3) Guns with .023
Gun:
 • Silver Plus Airless Gun
Hose:
 • 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II 3300 psi (227 bar)
 • 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II 3300 psi (227 bar)
Tip:
 • RAC X 527 Tip and Guard
 • RAC X WideRAC 1231
Inlet Strainer:
 • Part #257033
Pump Filter:
 • Includes Easy Out Pump Filter
Easy Out Filter Screens:
 • 30 Mesh - 244071
 • 60 Mesh - 244067
 • 100 Mesh - 244068
 • 200 Mesh - 244069
Sprayer Dimensions:
 • 33 (84) x 25 (63) x 38.5 (98)
Wear Parts:
 • Packing Kit - 248213
 • Chromex Rod - 249028
 • Cylinder - 196754
 • Sleeve - 257031
 • Intake Valve - 196753
 • Piston Valve - 240150
 • 30/55 Gallon Siphon Kit - 257353
Complete Pump Lower:
 • Part #257146
Manuals:
 • Instruction/Repair - 313313

Gas Product Specifications



GH 130 Convertible

- Max Tip:** .037
- Max psi/bar:** 3300/227
- Max gpm/lpm:** 1.3/4.9
- Engine:** 120 cc Honda
- Weight lbs/kg:** 150/68
- Electric Max Tip:** .031
- Electric Max Gpm/Lpm:** 1.1/4.2
- Gun Support:**
 - (1) Gun with .037
 - Electric:**(1) Gun with .031
 - Gun:**
 - Contractor Airless Gun
- Hose:**
 - 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II 3300 psi (227 bar)
- Tip:**
 - RAC X 517 Tip and Guard
- Crush Proof Strainer:**
 - Part #288472
- Pump Filter:**
 - Includes Easy Out Pump Filter
- Easy Out Filter Screens:**
 - 30 Mesh - 244071
 - 60 Mesh - 244067
 - 100 Mesh - 244068
 - 200 Mesh - 244069
- Sprayer Dimensions:**
 - 41 (104.1) x 24 (61) x 30 (76.2)
- Wear Parts:**
 - Packing Kit - 288471
 - Chromex Rod - 288479
 - Cylinder - 243347
 - Chromex Sleeve - 248210
 - Intake Valve - 244199
 - Piston Valve - 240150
 - 30/55 Gallon Siphon Kit - 287541
- Complete Pump Lower:**
 - Part #288466
- Manuals:**
 - Instruction - 311791
 - Repair - 311797



GH 200 Convertible

- Max Tip:** .047
- Max psi/bar:** 3300/227
- Max gpm/lpm:** 2.15/8.14
- Engine:** 160 cc Honda
- Weight lbs/kg:** 160/72
- Electric Max Tip:** .031
- Electric Max Gpm/Lpm:** 1.1/4.2
- Gun Support:**
 - (1) Gun with .047
 - (2) Guns with .034
 - (3) Guns with .027
 - (4) Guns with .023
 - Electric:**
 - (1) Gun with .031
 - (2) Guns with .017
 - Gun:**
 - Silver Plus Airless Gun
- Hose:**
 - 1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II 3300 psi (227 bar)
- Tip:**
 - RAC X 517 Tip and Guard
- Crush Proof Strainer:**
 - Part #288472
- Pump Filter:**
 - Includes Easy Out Pump Filter
- Easy Out Filter Screens:**
 - 30 Mesh - 244071
 - 60 Mesh - 244067
 - 100 Mesh - 244068
 - 200 Mesh - 244069
- Sprayer Dimensions:**
 - 41 (104.1) x 24 (61) x 30 (76.2)
- Wear Parts:**
 - Packing Kit - 287813
 - MaxLife Rod - 288469
 - Cylinder - 245413
 - MaxLife Sleeve - 249121
 - Intake Valve - 240918
 - Piston Valve - 249177
 - 30/55 Gallon Siphon Kit - 287541
- Complete Pump Lower:**
 - Part #288467
- Manuals:**
 - Instruction - 311791
 - Repair - 311797



GH 230 Convertible

- Max Tip:** .053
- Max psi/bar:** 3300/227
- Max gpm/lpm:** 2.35/8.9
- Engine:** 200 cc Honda
- Weight lbs/kg:** 168/75.6
- Gun Support:**
 - (1) Gun with .053
 - (2) Guns with .038
 - (3) Guns with .032
 - (4) Guns with .028
 - (5) Guns with .024
 - Electric:**
 - (1) Gun with .031
 - (2) Guns with .017
 - Gun:**
 - Silver Plus Airless Gun
- Hose:**
 - 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II 3300 psi (227 bar)
- Tip:**
 - RAC X 517 Tip and Guard
- Crush Proof Strainer:**
 - Part #288472
- Pump Filter:**
 - Includes Easy Out Pump Filter
- Easy Out Filter Screens:**
 - 30 Mesh - 244071
 - 60 Mesh - 244067
 - 100 Mesh - 244068
 - 200 Mesh - 244069
- Sprayer Dimensions:**
 - 48 (121.9) x 24 (61) x 32 (81.3)
- Wear Parts:**
 - Packing Kit - 287813
 - MaxLife Rod - 288470
 - Cylinder - 249532
 - MaxLife Sleeve - 287817
 - Intake Valve - 240918
 - Piston Valve - 249177
 - 30/55 Gallon Siphon Kit - 287541
- Complete Pump Lower:**
 - Part #288468
- Manuals:**
 - Instruction - 311791
 - Repair - 311797



GH 300

- Max Tip:** .057
- Max psi/bar:** 3300/227
- Max gpm/lpm:** 3.0/11.4
- Engine:** 270 cc Honda
- Weight lbs/kg:** 195/87.8
- Gun Support:**
 - (1) Gun with .057
 - (2) Guns with .039
 - (3) Guns with .033
 - (4) Guns with .029
 - (5) Guns with .025
 - (6) Guns with .023
 - Gun:**
 - Silver Plus Airless Gun
- Hose:**
 - 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II 3300 psi (227 bar)
- Tip:**
 - RAC X 517 Tip and Guard
- Crush Proof Strainer:**
 - Part #288472
- Pump Filter:**
 - Includes Easy Out Pump Filter
- Easy Out Filter Screens:**
 - 30 Mesh - 244071
 - 60 Mesh - 244067
 - 100 Mesh - 244068
 - 200 Mesh - 244069
- Sprayer Dimensions:**
 - 48 (121.9) x 24 (61) x 32 (81.3)
- Wear Parts:**
 - Packing Kit - 287813
 - MaxLife Rod - 288470
 - Cylinder - 249532
 - MaxLife Sleeve - 287817
 - Intake Valve - 240918
 - Piston Valve - 249177
 - 30/55 Gallon Siphon Kit - 287541
- Complete Pump Lower:**
 - Part #248468
- Manuals:**
 - Instruction - 311791
 - Repair - 311797



GH 733 & Roof Rigs

- Max Tip:** .060
- Max psi/bar:** 3500/240
- Max gpm/lpm:** 3.0/11.4
- Engine:** 624 cc Kohler
- Weight lbs/kg:** 480/217
- Gun:**
 - Silver Plus Airless Gun
- Hose:**
 - 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II HP 4000 psi (276 bar)
- Tip:**
 - RAC X 517 Tip and Guard
- Inlet Strainer:**
 - Part #237840
- Sprayer Dimensions:**
 - 48.5 (123.1) x 29 (73.6) x 50.5 (128.3)
- Wear Parts:**
 - Packing Kit - 244853
 - Rod - 15J096
 - Cylinder - 197318
 - Intake Valve - 197304
 - Piston Valve - 197312
- Complete Pump Lower:**
 - Part #L250C1
- Manuals:**
 - Instruction - 307616
 - Repair - 307616
- Optional Roof Rigs**
 - GH 1015 (965165)
 - 1000 psi/15.0 gpm
 - GH 2075 (965171)
 - 1800 psi/7.5 gpm
 - GH 2560 (965168)
 - 2400 psi/6.0 gpm
 - GH 3640 (687327)
 - 3600 psi/3.8 gpm
 - GH 5030 (687100)
 - 4900 psi/2.8 gpm



GH 833 Big Rig

- Max Tip:** .065
- Max psi/bar:** 4000/276
- Max gpm/lpm:** 4.0/15.1
- Engine:** 390 cc Honda
- Weight lbs/kg:** 350/158
- Gun Support:**
 - (1) Gun with .065
 - (2) Guns with .046
 - (3) Guns with .037
 - (4) Guns with .032
 - (5) Guns with .029
 - (6) Guns with .026
 - Gun:**
 - Silver Plus Airless Gun
- Hose:**
 - 3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II HP 4000 psi (276 bar)
- Tip:**
 - RAC X 655 Tip and Guard
- Inlet Strainer:**
 - Part #237840
- Pump Filter:**
 - Includes Easy Out Pump Filter
- Easy Out Filter Screens:**
 - 30 Mesh - 244071
 - 60 Mesh - 244067
 - 100 Mesh - 244068
 - 200 Mesh - 244069
- Sprayer Dimensions:**
 - 40 (101.6) x 27 (68.5) x 47 (119.3)
- Wear Parts:**
 - Packing Kit - 287835
 - MaxLife Rod - 287832
 - Cylinder - 287836
 - MaxLife Sleeve - 287833
 - Intake Valve - 287838
 - Piston Valve - 287837
 - Solvent Resistant Siphon Kit - 287915
- Complete Pump Lower:**
 - Part #287834
- Manuals:**
 - Instruction - 311279
 - Repair - 311280



ABOUT GRACO

PROVEN QUALITY. LEADING TECHNOLOGY.

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

GRACO LOCATIONS

MAILING ADDRESS

P.O. Box 1441
Minneapolis, MN 55440-1441
Tel: 612-623-6000
Fax: 612-623-6777

AMERICAS

MINNESOTA

Worldwide Headquarters
Graco Inc.
88-11th Avenue N.E.
Minneapolis, MN 55413

EUROPE

BELGIUM

European Headquarters
Graco N.V.
Industrieterrein-Oude Bunders
Slakweidestraat 31
3630 Maasmechelen,
Belgium
Tel: 32 89 770 700
Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA

Graco Australia Pty Ltd
Suite 17 2 Enterprise Drive
Bundoora Victoria 3083
Australia
Tel: 61 3 9467 8558
Fax: 61 3 9467 8559

CHINA

Graco Hong Kong Ltd.
Shanghai Representative Office
Room 118 1st Floor
No.2 Xin Yuan Building
No.509 Cao Bao Road
Shanghai, P.R. China 200233
Tel: 86 21 649 50088
Fax: 86 21 649 50077

INDIA

Graco Hong Kong Ltd.
India Liaison Office
Room 103, Level 4, Augusta Point
Golf Course Road
Gurgaon, Haryana, India 122001
Tel: +91 124 435 4208
Fax: +91 124 435 4001

JAPAN

Graco K.K.
1-27-12 Hayabuchi
Tsuzuki-ku
Yokohama City, Japan 2240025
Tel: 81 45 593 7300
Fax: 81 45 593 7301

KOREA

Graco Korea Inc.
Choheung Bank Building
4th Floor #1599
Gwanyang-Dong, Dongan-Ku,
Anyang-Si, Gyunggi-Do,
Korea 431-060
Tel: 82 31 476 9400
Fax: 82 31 476 9801

SALES/ DISTRIBUTION/ SERVICE

Call today for product information or to request a demonstration.

800-690-2894 or visit us at www.graco.com.

Graco Inc. is registered to I.S. EN ISO 9001

North America
Customer Service
800-690-2894
Fax 800-334-6955